

Uni Tube Cable CST Armoured

ID: **ZN01**




KABELOVNA Děčín Podmokly s.r.o.
Ústecká 840/33, 405 33 Děčín 5
Czech Republic
DIČ CZ26759993
tel.: +420 412 706 222
www.kabelovna.cz

26. 4. 2021 ver. 1

J/A-DQ(BN)B(SR)H max. 12F

This cable is suitable for indoor or outdoor installation.



Mechanical and Environmental properties

Test	Value	Unit	Method
Cable outer diameter	10,1 ± 0,4	mm	EN 60811-203
Cable weight	122	kg/km	
Outer jacket thickness	1,3	mm	
Loose tube diameter	3	mm	
Max. tensile strength	2500	N	EN 60794-1-21-E1
Crush resistance test	10000	N	EN 60794-1-21-E3
Impact resistance test	30	Nm	EN 60794-1-21-E4
Min. bend radius (no load)	15	× OD	EN 60794-1-21-E11a
Min. bend radius (load)	20	× OD	EN 60794-1-21-E11b
Moisture resistance test	pass		EN 60794-1-22-F5
Temperature range	Installation	-15 to + 50	°C
	Operation	-20 to + 70	
	Storage	-20 to + 70	
Fire properties – Flammability	pass		EN 60332-3-22 (cat.A)
Fire properties – Acid gases	pass		EN 60754-1
	pass		EN 60754-2
Fire properties – Smoke density	pass		EN 61034-1
	pass		EN 61034-2

Cable life time - minimum 30 years

Sheat Marking

Print colour	White
Print method	INK-Jet
Print legend	Manufacturer's name, job number, type of cable, length marking @ 1 m intervals

Other print legends available on request

Fibre colour coding

According to IEC 60304

1	Red	7	Brown
2	Green	8	Violet
3	Blue	9	Turquoise
4	Yellow	10	Black
5	White	11	Orange
6	Grey	12	Pink

*with black rings

Other fibre colour sequences available on request

Packing

Depending on ordered put-up lengths

