

# TERMINAL CONNECTION

## OTO<sub>2</sub> (Optical Termination Outlet)

### PRODUCT + BENEFITS

- + **Compact enclosure**
- + **Up to 4 SC/APC connectors and 4 pigtails**
- + **Can be mounted on all types of structures**
- + **The mounting holes are completely separated from the area where the cables are coiled and spliced**

### PRESENTATION

The OTO (Optical Terminal Outlet) marks the end of the operator's network. It is mounted at the entrance to the dwelling, usually on a wall or inside the communications cabinet.

The mounting holes are completely separated from the area where the cables are coiled and spliced, making OTO<sub>2</sub> particularly easy to use. The base of the enclosure is where the mounting holes and cable routing and anchoring guides are located. All of the fiber optic components are located in the cassette.

This makes it less likely to damage fibers when mounting the outlet. And, because the cassette can be unclipped from the base, it is easy to access the fiber optic connections later if needed.

The outlet can be mounted using double-sided adhesive tape, screw-mounted to a wall, installed in a flush-mount wall box, or clipped onto a DIN rail.

And, with five cable routing options, the outlet is simple to install along a baseboard, on a wall, or in a flush-mount wall box.



# TERMINAL CONNECTION

## OTO<sub>2</sub> (Optical Termination Outlet)

### PERFORMANCE

<b>Dimensions</b>	80 mm x 83 mm x 28 mm
<b>Color</b>	White RAL9010
<b>Mounting options</b>	<ul style="list-style-type: none"> <li>- Double-sided adhesive</li> <li>- Flush-mount wall box</li> <li>- Wall anchors/screws</li> <li>- DIN rail</li> </ul>
<b>Number of cable entries</b>	<ul style="list-style-type: none"> <li>- 2 on side for baseboard-mounted installation</li> <li>- 2 on top for wall-mounted installation</li> <li>- 1 on back for for installation in flush-mount wall box</li> <li>- 1 on bottom for larger-diameter external cables</li> </ul>
<b>Connectors</b>	SC Simplex or LC Duplex
<b>Pigtails</b>	Length 80 cm; G657A2 fiber; IL < 0.3 dB; RL >55 dB
<b>Capacity</b>	4 30 mm or 40 mm heat-shrink splice protectors

### ORDERING INFORMATION

Product no.	Description	Unit
MO411	OTO <sub>2</sub> 1OF SC/APC + PIGTAIL	1
MO421	OTO <sub>2</sub> 2OF SC/APC + PIGTAIL	1
MO441	OTO <sub>2</sub> 4OF SC/APC + PIGTAIL	1

Omelcom is committed to providing superior service and product performance. The product features in this document are subject to change without notice.